



USB Plug Adapter with 2 AC Outlets and Type A & Type C USB Wall Charger

FEATURES

- Type A & Type C USB Ports with a total output of 4.2 Amp 5V DC (2.4 A maximum output for type A single port/3.0 A maximum output for type C single port). The inside Smart Chip could identify and optimize the charging current of your devices. Two USB ports provide high-speed charging, compatible with iPhone, iPod, Samsung Galaxy/Note, Android mobile phones, E-readers, game systems, tablets, headsets and digital cameras, etc.
- A non-grounding 2 prong outlet can be transferred to receive two 3 prong outlets with grounding protection, perfect for older houses or offices with AC wall outlets that can not accept grounded plugs.
- Horizontal design will not block the other outlet of the single gang receptacle which saves space and cord clutter. Perfect for your bathroom and kitchen, and the white finish easily integrates into any decoration. The small and compact size makes it easy to carry in your toolkit or laptop bag anywhere.
- Grounded protection is maintained by connecting the metal clip on this adapter outlet to the middle screw on the faceplate of a grounded outlet box. Slidable grounding ring fits different fixing hole spacing of the wall plate.

SPECIFICATIONS

Model: EA02101CAG1

Certification	ETL , FCC
Standard	UL498A, UL1310
Operating Temperature Range	-10°C to 40°C
Storage Temperature	-40°C to 85°C
Rating Input	15A 125VAC
Rating Wattage	1875W
Cover and body material	Thermoplastic
Flammability	V-2 per UL94
Color	White
USB Type	Dual Type A USB Ports / Type A & Type C USB Ports (optional)
USB Output	5V 4.2A MAX, 2.4A MAX Type A Single Port, 3.0A MAX Type C Single Port

