









Outlet Adapter Type GFCI

FEATURES

- · Versatile Portable GFCI adapter is a great way to take safety with you and is suitable for indoor use in your bathroom, kitchen, basement and garage
- Performed 6000+ times factory test, which is twice the testing times of UL standard. Feature surge protection and lightning protection function withstanding 6 kilovolt.
- · Self-test within 5 seconds when power is on and repeated self-test every 5 seconds with high reliability and high anti-interference performance
- · Low power consumption and long service life. The impact-resistant body provides superior performance and safety.
- UL and CUL listed
- Easily see that power is available with the "power on" indicator light

SPECIFICATIONS

Safety Certification	UL,CUL Certification
Application Standard	UL943/CSA 22.2 No. 144.1
	UL498/CSA 22.2 No.42
Plug type	5-15P
Outlet type	5-15R (5-15P,1-15P applicable)
Operating Temperature Range	-35°C ~ +66°C
Rated Voltage	125Vac
Rated Current	GFCI 15A
Rated Frequency	60Hz
Rated Residual Operating Current	4mA ~ 6mA
Action Time for the Residual Current	T= (20/I) ^{1.43} mS
	6mA, ≤1s; 264mA, ≤25ms
Endurance	≥6000 times (3000 in UL standard)
Voltage Surge Withstand	6KV/3KA
Colors	per clients' demands
Reset	Auto-reset type and manual reset type could be configured as per client's demand
UL listed	UL certifications: configured as per client's demand before delivery
	ւ <mark>Մ</mark> L us ւ ՄL ՄL





