



Appliance Leakage-current Interrupter



FEATURES

- Shut down the power to the appliance when there is a ground fault current of 6mA or more but not less than 4mA
- Accepted by either UL or ETL approved appliances
- Exquisite appearance and compact design meet the aesthetic perspective which appealing for consumer, especially females
- Covered by intellectual property and patents and comply with UL943B new standard requirement with self-test function and conduct auto-monitor function every 5 seconds
- "TWO-IN-ONE" dual voltage model, provides both regular 120V and 240V to avoid any possible hurt when the unwanted voltage plug in
- High impact resistant, thermoplastic construction for superior strength and durability
- Safe power denying feature applies the cutting-edged technology in the self-testing requirements
- Built-in reset button indication light shows green color during normal operation for easy identification
- Spiral cord grommet for great torsion resistance
- Widely applies to the household appliances such as hair dryers, bathroom heaters, carpet cleaning machines, hair straighteners, curlers, etc

SPECIFICATIONS

Model:AL18

Safety Certification	UL Certification
Application Standard	UL943B
Rated Voltage	125V/250V
Rated Current	10A/13A/15A
Rated Frequency	60Hz
Residual Operating Current	4~6mA
Tripping Time	≤25ms
Plug Configuration	1-15P
Indication Light	Green
Applicable Cord Set	Customizable
Color	Customizable

